


RECOMMENDED PCB LAYOUT(PCB THICKNESS: 1.6mm)
COMPONENT SIDE VIEW(TOLERANCE: ±0.05)

1. MATERIAL:
- 1.1 Insulator: PBT, UL94V-0.
Insulator Color: Black.
 - 1.2 Sleeve: Brass, 15u" Tin Plated Overall.
 - 1.3 Tip Terminal: Phosphor Bronze, 10u" Silver Plated Over 30u" Min. Nickel Underplated Overall.
 - 1.4 Earth Fitting: Brass, 15u" Tin Plated Over 30u" Copper Underplated Overall.
 - 1.5 Terminal: Phosphor Bronze, 10u" Silver Plated Over 30u" Min. Nickel Underplated Overall.
 - 1.6 Spring: Stainless Steel, SUS301.
2. SPECIFICATION:
- 2.1 Voltage Rating: DC 16V.
 - 2.2 Current Rating: 0.3A
 - 2.3 Contact Resistance: 50mΩ Max.
 - 2.4 Insulation Resistance: 100MΩ Min.
 - 2.5 Withstanding Voltage: AC 500V Per Minute.
 - 2.6 Operating Temperature: -25°C ~ +70°C.
3. NOTES:
- 3.1 This component and its homogeneous subcomponents are RoHS 6/6 compliant.
 - 3.2 Resistance to soldering heat: 265°C for 5 Seconds, And only for wave soldering process.(The Post will be Melted)

CUST P/N: 196731

REV.	DESCRIPTION	ECN NO.	NAME	DATE
G2	MODIFY DIMENSION	N1210010	Julia	Nov.09.2012
G1	MODIFY LOCATION OF LOGO	N1202025	Kevin	Mar.07.2012
G	ADD CPC MARK AND DIMENSION ETC.	N1012026	Karen	Dec.21.2010
A0	NEW RELEASE		Adam	Sep.28.2006

REVISIONS



TITLE: MINIATURE JACK OVER MINI DIN 4P COMBO CONNECTOR		DRAWN: Julia	CHECKED: Kevin	APPROVED: Peter	RFQ NO.:
DWG. NO.:	C-DIR0040P8T1-A10-RS1				
PART NO.:	DIR0040P8T1-A10-RS1				
UNIT:	mm	SCALE:	none	SHEET:	1 OF 1
DWG. SIZE:	A4	LAYER:	CN136		

