



- NOTES:
- MATERIAL:
 - INSULATOR: LCP, UL94V-0, COLOR: BLACK.
 - CONTACTS: COPPER ALLOY,
 - SHELL: COPPER ALLOY.
 - FINISH:
 - CONTACTS: GOLD(SEE TABLE) PLATED ON CONTACT AREA, 80μ" MIN. TIN PLATED ON SOLDER AREA, 30μ" MIN. NICKEL UNDERPLATED OVERALL.
 - SHELL: 50μ" MIN. NICKEL PLATED ENTIRE.
 - SPECIFICATIONS:
 - CURRENT RATING: 0.5A.
 - CONTACT RESISTANCE: 30mΩ MAX.
 - INSULATION RESISTANCE: 100MΩ MIN.
 - DIELECTRIC WITHSTANDING VOLTAGE: AC 500V/MINUTE.
 - OPERATING TEMPERATURE: -20°C TO +85°C.
 - OTHERS:
 - THIS COMPONENT AND ITS HOMOGENEOUS SUB COMPONENTS ARE RoHS & HALONGEN-FREE COMPLIANT.
 - RESISTANCE TO SOLDERING HEAT 265°C FOR 10 SECONDS.

30μ"	ACNHM220016-006
15μ"	ACNHM220016-005
10μ"	ACNHM220016-004
5μ"	ACNHM220016-003
3μ"	ACNHM220016-002
G/F	ACNHM220016-001
PLATING	CPC P/N.

REV.	DESCRIPTION	ECN NO.	NAME	DATE	DIM.	TOL.
A0	FIRST RELEASED	-	Owen	09-Feb-2015	X.	± -
					X.X	± 0.30
					X.XX	± 0.25
					X.XXX	± 0.15
					ANGL	± 3°

TITLE: HDMI 19P FEMALE RIGHT ANGLE SMT, SHORT TAB			
DWG. NO.: C = ACNHM220016			
UNIT: mm	DWG SIZE: A4	SCALE: none	SHEET: 1 OF 1

DRAWN: Owen	
CHECKED: Vic	
APPROVED: Peter	
RFQ NO.: Q1412090	